

C15 ACERT
365 ekW/ 456 kVA/ 60 Hz/ 1800 rpm/ 600 V/ 0.8 Power Factor

Rating Type: PRIME

Emissions: U.S. EPA Certified for Stationary Emergency Use Only (Tier 3 Nonroad Equivalent Emission Standards)



C15 ACERT
365 ekW/ 456 kVA
60 Hz/ 1800 rpm/ 600 V

Image shown may not reflect actual configuration

Metric English

Package Performance		
Genset Power Rating with Fan @ 0.8 Power Factor	365 ekW	
Genset Power Rating	456 kVA	
Aftercooler (Separate Circuit)	N/A	N/A

Fuel Consumption		
100% Load with Fan	110.3 L/hr	29.1 gal/hr
75% Load with Fan	91.0 L/hr	24.0 gal/hr
50% Load with Fan	66.2 L/hr	17.5 gal/hr
25% Load with Fan	38.3 L/hr	10.1 gal/hr

Cooling System ¹		
Engine Coolant Capacity	N/A	N/A

Inlet Air		
Combustion Air Inlet Flow Rate	36.9 m ³ /min	1303.2 cfm
Max. Allowable Combustion Air Inlet Temp	48 ° C	119 ° F

Exhaust System		
Exhaust Stack Gas Temperature	479.4 ° C	894.9 ° F
Exhaust Gas Flow Rate	96.2 m ³ /min	3395.2 cfm
Exhaust System Backpressure (Maximum Allowable)	10.0 kPa	40.0 in. water



C15 ACERT
365 ekW/ 456 kVA/ 60 Hz/ 1800 rpm/ 600 V/ 0.8 Power Factor

Rating Type: PRIME

Emissions: U.S. EPA Certified for Stationary Emergency Use Only (Tier 3 Nonroad Equivalent Emission Standards)

Heat Rejection		
Heat Rejection to Jacket Water	155 kW	8819 Btu/min
Heat Rejection to Exhaust (Total)	429 kW	24376 Btu/min
Heat Rejection to Aftercooler	98 kW	5578 Btu/min
Heat Rejection to Atmosphere from Engine	69 kW	3937 Btu/min
Heat Rejection to Atmosphere from Generator	26 kW	1467 Btu/min

Alternator²	
Motor Starting Capability @ 30% Voltage Dip	1057 skVA
Current	439 amps
Frame Size	LC6124B
Excitation	AR
Temperature Rise	125 ° C

Emissions (Nominal)³		
NOx	1455.3 mg/Nm ³	3.2 g/hp-hr
CO	272.0 mg/Nm ³	0.6 g/hp-hr
HC	19.5 mg/Nm ³	0.1 g/hp-hr
PM	16.3 mg/Nm ³	0.0 g/hp-hr

DEFINITIONS AND CONDITIONS

1. For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.
2. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.
3. Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.



**C15 ACERT
365 ekW/ 456 kVA/ 60 Hz/ 1800 rpm/ 600 V/ 0.8 Power Factor**

Rating Type: PRIME

**Emissions: U.S. EPA Certified for Stationary Emergency
Use Only (Tier 3 Nonroad Equivalent Emission Standards)**

Applicable Codes and Standards:

AS1359, CSA C22.2 No100-04, UL142,UL489, UL869, UL2200,
NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528,
NEMA MG1-22,NEMA MG1-33, 2006/95/EC, 2006/42/EC, 2004/108/EC.

Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

PRIME:Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

Fuel Rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

www.Cat-ElectricPower.com

Performance No.: DM8150-05

Feature Code: C15DECD

Generator Arrangement: 4183889

Date: 02/09/2016

Source Country: U.S.

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.